Revision Date 09/02/2021

SECTION 1. IDENTIFICATION

Product name : FS HTB FLUID (Canada)

Manufacturer or supplier's details

Forsythe Lubrication Associates Ltd 120 Chatham Street Hamilton ON L8P 2B5 Canada Telephone : 1-905-525-7192

Emergency telephone number

Emergency telephone number : CANUTEC 1-888-226-8832 Poison Control Centre: Consult local telephone directory for emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use	:FS HTB Fluid is a high-quality, multifunctional fluid, specially
	formulated for use in transmissions, final drives, wet brakes, and
	hydraulic systems of tractors and other equipment employing a
	common fluid reservoir.

Prepared by : Operations: 1 905-572-7192

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Potential Health Effects

Primary Routes of Entry : Eye contact Ingestion

Ingestion Inhalation Skin contact

Aggravated Medical Condition: None known.

Other hazards

None known.

Revision Date 09/02/2021

IARCNo component of this product present at levels greater than or
equal to 0.1% is identified as probable, possible or confirmed
human carcinogen by IARC.ACGIHNo component of this product present at levels greater than or
equal to 0.1% is identified as a carcinogen or potential
carcinogen by ACGIH.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

eempenence		
Chemical name	CAS-No.	Concentration (% w/w)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	45 - 65
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	72623-86-0	20 - 50
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	0.1 – 1
Distillates (petroleum), solvent- dewaxed heavy paraffinic	64742-65-0	1 - 5
Distillates (petroleum), solvent dewaxed light paraffinic; baseoil unspecified	64742-56-9	>0.1
Calcium long-chain alkaryl sulfonate	Proprietary	0.1 -1
Phosphorodithioic acid, mixed O,O- bis (2-ethylhexyl and iso-Bu and pentyl) esters, zinc salts	68988-29-8	1 - 5
Phenol, (tetrapropenyl) deriva-tives	74499-35-7	0.01 - 0.05

SECTION 4. FIRST AID MEASURES

:

If inhaled

Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.

SAFETY DATA SHEET

FS HTB FLUID

Revision Date 09/02/2021

In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during firefighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion products	:	Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), sulphur compounds (H2S), zinc oxides (ZnOx), metal oxides, hydrocarbons, smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions	:	Do not allow uncontrolled discharge of product into the environment.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: None known.
Advice on safe handling	 For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	 Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Revision Date 09/02/2021

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhalable fraction)	5 mg/m3	ACGIH

Engineering measures : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	organic vapour filter
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Revision Date 09/02/2021

Eye protection	:	Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Protective measures	:	Wash contaminated clothing before re-use.
Hygiene measures	:	Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: viscous liquid
Colour	: light brown
Odour	: Mild petroleum oil like.
Odour Threshold	: No data available
рН	: No data available
Pour point	: -45 °C (-47 °F)
Boiling point/boiling range	: No data available
Flash point	: 235 °C (448 °F) Method: Cleveland open cup

Fire Point	: No data available
Evaporation rate	: No data available
Auto-ignition temperature	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available

Revision Date 09/02/2021

Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8598 kg/l (15 °C / 59 °F)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: noctanol/water	:	No data available
Viscosity Viscosity, kinematic	:	57.7 cSt (40 °C / 104 °F) 9.5 cSt (100 °C / 212 °F)
Explosive properties	:	Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidizing agents and reducing agents.
Hazardous decomposition products	:	May release COx, H2S, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological	effects
Information on likely routes of exposure	: Eye contact Ingestion Inhalation Skin contact
Acute toxicity <u>Product:</u> Acute oral toxicity	: Remarks: No data available

SAFETY DATA SHEET

FS HTB FLUID

Revision Date 09/02/2021

Acute inhalation toxicity	: Assessment: The substance or mixture has no acute inhalation toxicity Remarks: No data available
Acute dermal toxicity	: Assessment: The substance or mixture has no acute dermal toxicity Remarks: No data available
<u>Components:</u> lubricating oi neutral oil-based:	ls (petroleum), C20-50, hydrotreated
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,
lubricating oils (petroleum) Acute oral toxicity	, C15-30, hydrotreated neutral oil-based: : LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,
distillatos (notroloum), solv	ent-dewaxed heavy paraffinic:
Acute oral toxicity	: LD50 (Rat): $>$ 5,000 mg/kg,
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg,
Phosphorodithioic acid,mixe	ed O,O-bis(2-ethylhexyland iso-Bu and iso-Pr) esters,zinc salts : Rat 125 mg/kg - Sub-acute NOAEL Oral
Calcium long-chain alkaryl S	ulfonate : Rabbit >5000 mg/kg LD 50 Dermal Rat >50000mg/kg LD 50 Oral
Phenol, (tetrapropenyl) deriv	atives
	:Rat 15mg/kg - Sub-chronic NOAEL Oral :Rat 100mg/kg - Chronic NOAEL Oral
Skin corrosion/irritation	
<u>Product:</u> Remarks	: No data available
Serious eye damage/eye irr	itation
Product:	
Remarks	: No data available

Revision Date 09/02/2021

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Eco toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other : Remarks: No data available aquatic invertebrates

Toxicity to algae	: Remarks: No data available
-------------------	------------------------------

Toxicity to microorganisms : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bio accumulative potential

No data available

Mobility in soil

No data available

Revision Date 09/02/2021

Other adverse effects No data available **SECTION 13. DISPOSAL** CONSIDERATIONS

Disposal methods

Waste from residues

: The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations IATA-DGR Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

National Regulations TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:DSL:On the inventory, or in compliance with the inventory		
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION

Full text of other abb	reviations	
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table
		2: OEL)

Revision Date 09/02/2021

CA QC OEL

CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA CA AB OEL / TWA CA AB OEL / STEL CA QC OEL / TWAEV CA QC OEL / STEV	:	8-hour, time-weighted average 8-hour Occupational exposure limit 15-minute occupational exposure limit Time-weighted average exposure value Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan);

ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD -Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bio accumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States): UN - United Nations: UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bio accumulative; WHMIS - Workplace Hazardous Materials Information System

I 905-525-7192
I.

Revision Date

: 2020/01/03

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET

FS HTB FLUID

Revision Date 09/02/2021

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN